

# Zero Sightline—Series 30P

## Product Data

### Description

**AAMA CATEGORY** – Architectural

**AAMA/W Designation** – AW-75

**Configuration** – Outward Projected, Outswing Casement

**Series** – 30P

### AAMA Air, Water & Structural Testing

**Test Size** – AAMA 101 for Designation and/or Configuration

**Allowable Air** – MAX 0.10 CFM/LF @ 6.24

**Uniform Load Deflection** – 75 PSF

**Water** – 15 PSF

**Uniform Load Structural** – 112.5 PSF

### CRF & 'U' Value

**CRF Class** – CRF 55

**U-Value Class** – .44-.65

### Construction – Frame

**Minimum Wall Thickness** – 0.125"

**Minimum Wall Thickness @ Fasteners** – 0.125"

**Depth** – 3"

**Fabrication** – Mitered, Epoxied and Crimped

**Design** – Flat or CW Insert Leg

w/Alum Corner Blocks

### Construction – Primary Operable

**Minimum Wall Thickness** – 0.125"

**Minimum Wall Thickness @ Fasteners** – 0.125"

**Depth** – 3"

**Design** – Flush w/Frame, Tubular

**Fabrication** – Mitered, Epoxied and Crimped w/Alum Corner Blocks

### Thermal Barrier

**Separation** – 1/4"

**Design** – Poured In Place Polyurethane

### Optional Window Components

**Screens** – Flat Or Wicket

### Hardware

**As Specified** – Select From Hardware Section

### Weather-Stripping

**Primary Operable** – Two Rows, Dual Durometer, Compression EPDM

### Glazing – Operable Units

**Location** – Factory or Field

**Method** – Structural Silicone

### Finish

**As Specified** – Anodized or Painted

### Warranty

**As Specified** – 2, 5 or 10 Years

